








高温尼龙轮

特别性能:

- 采用独特配方的尼龙材料一次性注塑成型, 具有耐高温、耐重等功能
- 圆弧形双轨道设计, 使支架更耐重、更灵活、更具有实用性
- 表面烤漆处理, 抗腐蚀能力强
- 使用温度为-10~280℃, 适合在高温环境中使用



订货号	型号	 轮径(mm)	 轮宽(mm)	 承载(kg)	 安装高度(mm)	 转动半径(mm)	 刹车转动半径(mm)	 安装尺寸(mm)	 丝杆规格(mm)
122711075	① 固定型脚轮	75 (3")	32	73	107	73	103	(A)75x45 (B)95x66	M12x25
122712075	② 万向型脚轮								
122713075	③ 万向型脚轮 带刹车								
122714075	④ 万向型脚轮 带螺纹插								
122711100	① 固定型脚轮	100(4")	32	105	130	87	111	(A)75x45 (B)95x66	M12x25
122712100	② 万向型脚轮								
122713100	③ 万向型脚轮 带刹车								
122714100	④ 万向型脚轮 带螺纹插								
122711125	① 固定型脚轮	125(5")	32	115	155	100	119	(A)75x45 (B)95x66	M12x25
122712125	② 万向型脚轮								
122713125	③ 万向型脚轮 带刹车								
122714125	④ 万向型脚轮 带螺纹插								