




尼龙脚轮

- 免维护, 低噪音, 高强度, 耐磨损
- 镀锌钢板轮架, 旋转轴承带双珠滚道
- 适用温度范围: -20°C 至 $+80^{\circ}\text{C}$
- 普通轴承与滚珠轴承两种可供选



旋转轴承



脚轮直径 Φ x宽(mm)			65x30	80x35	100x38	125x38	150x40	200x50
最大负载(kg)			100	150	200	200	350	350
总高度(mm)			93	100	125	155	185	235
万向轮偏距(mm)			36	36	38	38	52	54
轮架顶盖尺寸	万向型脚轮(mm)		100x70	105x80	105x80	105x80	135x110	135x110
	固定型脚轮(mm)		100x70	102x87	102x87	102x87	135x114	135x114
螺栓孔间距(mm)			75x45	76-80x60	76-80x60	76-80x60	105x75-80	105x75-80
螺栓孔直径 Φ (mm)			9	9	9	9	11	11
轮毂长度/中心孔直径(mm)			40/12	40/12	40/12	50/15	60/20	60/20
普通轴承	1 万向型脚轮	订货号	122701862	122701863	122701864	122701865	122701866	122701867
	2 万向型脚轮带刹车	订货号	-	122701868	122701870	122701871	122701872	122701873
	3 固定型脚轮	订货号	122701874	122701875	122701876	122701878	122701879	122701880
	4 单轮	订货号	122701881	122701882	122701883	122701884	122701888	122701887
滚珠轴承	1 万向型脚轮	订货号	-	122701895	122701896	122701897	122701898	122701899
	2 万向型脚轮带刹车	订货号	-	122701900	122701901	122701902	122701903	122701904
	3 固定型脚轮	订货号	-	122701905	122701906	122701908	122701909	122701910
	4 单轮	订货号	-	122701911	122701912	122701913	122701914	122701916



尼龙脚轮

- 高强度, 耐磨损
- 耐酸碱腐蚀
- 适用温度范围: -40°C 至 $+90^{\circ}\text{C}$
- 热塑性塑料, 以尼龙为主要成分
- 普通轴承与滚珠轴承两种可供选



脚轮直径 Φ x宽(mm)			80x30	100x35	125x45	150x40	200x50
轮毂长度(mm)			35	50	53	55	52
普通轴承	最大负载(kg)		250	450	550	850	1100
	中心孔直径(mm)		20	15	15	20	20
	订货号		122701924	122701925	122701926	122701927	122701928
滚珠轴承	最大负载(kg)		-	500	600	900	1100
	中心孔直径(mm)		-	12	20	20	20
	订货号		-	122701929	122701930	122701932	122701933

