



弹性轮胎

- 耐磨损, 旋转阻力较小
- 轮辐为镀锌钢板材质
- 镀锌格钢板轮架, 旋转轴承带双球滚道, 滚道上有附加垫圈
- 适用温度范围: -5°C 至 $+80^{\circ}\text{C}$
- 滚珠轴承



脚轮直径 Φ ×宽(mm)		125x38	140x38	160x40	180x50	200x50	250x60
最大负载(kg)		120	150	225	300	300	450
总高度(mm)		155	170	190	215	235	290
万向轮偏距(mm)		36	40	52	60	54	70
轮架顶盘尺寸	万向型脚轮(mm)	105x80	120x80	135x110	140x110	135x110	175x175
	固定型脚轮(mm)	102x87	120x80	135x114	140x110	135x114	230x130
螺栓孔尺寸	万向型脚轮(mm)	76-80x60	86x56	105x75-80	105x75-80	135x75-80	140x140
	固定型脚轮(mm)	76-80x60	96x56	105x75-80	105x75-80	135x75-80	190x75
螺栓孔直径 ϕ (mm)		9	9	11	11	11	14.5
脚轮	轮毂长度(mm)	50	50	60	60	60	75
	轮毂中心孔直径(mm)	15	15	20	20	20	25
1 万向型脚轮	订货号	122716218	122790497	122790527	122791507	122791531	122791604
2 万向型脚轮带刹车	订货号	122716220	122751782	122751790	122751804	122751812	122751820
3 固定型脚轮	订货号	122716221	122789839	122789855	122790624	122790640	122790683
4 脚轮	订货号	122716222	122790578	122790584	122791639	122791655	122791701



实心橡胶轮胎

- 镀锌格钢板轮架, 旋转轴承带双球滚道, 滚道上有附加垫圈
- 塑料轮辐比钢板轮辐更经济实用
- 适用温度范围: -5°C 至 $+80^{\circ}\text{C}$
- 满足中、轻型负载的搬运需求
- 滚珠轴承



脚轮直径 Φ ×宽(mm)		80x25	100x30	125x38	140x38	160x40	200x50
最大负载(kg)		50	70	100	115	135	205
总高度(mm)		100	125	155	170	190	235
万向轮偏距(mm)		36	38	38	40	55	54
轮架顶盘尺寸	万向型脚轮(mm)	105x80	105x80	105x80	120x80	137x105	135x110
	固定型脚轮(mm)	102x87	102x87	102x87	120x80	135x115	135x114
螺栓孔尺寸(mm)		76-80x60	76-80x60	76-80x60	96x56	75-80x105	75-80x105
螺栓孔直径 ϕ (mm)		9	9	9	9	11	11
轮毂长度/中心孔直径(mm)		40/12	40/12	50/15	50/15	60/20	60/20
1 万向型脚轮	订货号	122790314	122790179	122790209	122790233	122790278	122791051
2 万向型脚轮带刹车	订货号	122791553	122791561	122791588	122791596	122791618	122791634
3 固定型脚轮	订货号	122789987	122789871	122789901	122789938	122789952	122790748
4 脚轮	订货号	122704688	122790047	122704693	122790098	122790128	122790850

